



Category 2  
Medium Appliance  
6 Person Crew Cab

## Category 2 Specifications

CAB CHASSIS:	4x4 Crew Cab
G.V.M.:	10,000 kg.
DIMENSIONS:	Length 7600 mm, Width 2470 mm, Height 3050 mm (nominal)
TURNING CIRCLE:	17.7m
WHEEL BASE:	4200 mm
SEATING:	6 Persons
ENGINE:	6 cylinder OHC turbo diesel 7790 cc Displacement
POWER:	141 kW @ 2400 rpm
TORQUE:	582 Nm @ 1500 rpm
TRANSMISSION:	Gearbox: manual 6 speed overdrive, constant mesh, synchromesh 2nd-6th. Ratios: 6.72, 4.24, 2.58, 1.54, 1.00, 0.76 to 1. Reverse 6.82:1. Transfer Case: 2 speed. Ratios: High - 1.000:1, Low -2.091:1 Part time 4WD No-Spin Differential in Rear Axle.
MAIN PUMP:	Three stage centrifugal pump close coupled to a 2 cylinder 24 kW Silentpack diesel engine.
PUMP DUTY:	1000 litres/min. max. flow 800 litres/min. @ 700 kPa 650 litres/min. @ 900 kPa Closed pump pressure: 1450 kPa. Note:- Pump may exceed duty points stated.
PRIMER:	Electric rotary vane primer.
AUX. PUMP:	Single stage pump close coupled to single cylinder petrol engine.
TANK:	2000 litre galvanised steel tank.
FOAM:	Foam induction proportioner with 40 litre foam concentrate storage.
BODY:	Fully galvanised steel tray frame with aluminium treadplate floor. Modular aluminium lockers (3) and heatshield. Optional grasslands spraybar and dual pump controls in work area. Two live hosereels, 25 mm x 50 m hose n/side, 20 mm x 60 m hose o/side. Storage for canvas hose, branches, knapsacks, rakehoes, drip torches, extinguishers and standpipe.
PROTECTION SPRAY:	Single point water/foam spray on cab and on each wheel.



Head Office

Locked Mail Bag 17 Granville NSW 2142, Australia

website: [www.rfs.nsw.gov.au](http://www.rfs.nsw.gov.au)

**NSW RURAL FIRE SERVICE**  
*...for our community*